

► Model 226V-52 & 226V-61 Specifications

[Print](#) | [Compare Models](#)

ENGINE

Type/Horsepower/Cylinders	Briggs & Stratton Professional Series, 26 hp, V-Twin
Displacement	44.0 cu. in. (724 cc)
Lubrication System	Pressure Lube/Filter
Crankshaft	Vertical
Cooling System	Air
Fuel	Gasoline - unleaded
Fuel Capacity	12 U.S. Gal. (45.4 l)
Optional Fuel Capacity	NA
Air Cleaner	Dry element with pre-cleaner
Muffler	Ultra quiet, single, industrial type.

DURAMAX® DECKS

DECK	*
Mulching Package #	504567(52), 504569(61)
DURAMAX®; DECK SIZE	
– 41" Deck	NA
– 44" Deck	NA
– 48" Deck	NA
– 52" Deck	*
– 61" Deck	*
– 72" Deck	NA

CUTTING HEIGHT RANGE 1.0 to 5.0 in. (2.5cm to 12.7 cm)

Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane – 30% thicker than 1/4-in. (7.97 mm) – and (3) Sentry™ spindles with 8-inch spindle flanges, with 6-bolt pattern. Geometrically engineered design with 7-gauge skirts withstands the brunt of commercial mowing.

CONSTRUCTION (Robotic-welded steel)

BLADES (Tempered, alloy steel)	
– 41" Deck	NA
– 44" Deck	NA
– 48" Deck	NA
– 52" Deck	(3) 18 in. (45.7 cm)
– 61" Deck	(3) 21 in. (53.3 cm)
– 72" Deck	NA

SPINDLE ASSEMBLIES

2.5 cm (approx. 1 in.) O.D. shaft. Sentry™ spindle system to eliminate fiber wrap. Double bearings, non-greasable.

SPINDLE HOUSINGS

Machined aluminum housing.

BLADE DRIVE

Belt drive with single Kevlar V-belt and idler arm tensioning.

TRIMABILITY (Outside of std. tire to left trim side)	
– 41" Deck	NA
– 44" Deck	NA
– 48" Deck	NA
– 52" Deck	NA
– 61" Deck	NA
– 72" Deck	NA

STARTER & ELECTRICAL SYSTEM

Battery (maintenance-free)	12 Volt
Starter	Solenoid shift
Ignition	Breakerless

Prevents engine start when PTO clutch is engaged or steering

Interlock System		levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.
ULTIMATE OPERATOR STATION		
Seat		Spring suspension contoured cushion with foldable armrests.
Suspension		Roomy footrest with Shock Impact Reduction System (SIRS™).
Console-mounted Instruments		Hour meter, parking brake indicator light, ignition switch, choke and push/pull PTO switch.
Work Lights		Optional, plug-in ready
Hour Meter		Standard
TRANSMISSION & STEERING		
Type		Design-matched H1 hydrostatic transmission system with inline cooling fans, hydro fluid reservoir, Parker variable displacement piston-type pumps and Parker high-torque wheel motors.
Filtration		7 micron absolute, spin-on
Speed		0 - 9.0 mph (0 - 14.5 kph) forward 0 - 6.0 mph (0 - 9.7 kph) reverse
Turning Radius		True zero degree, turns within own length with counter-rotating, independently powered drive wheels.
Steering		One- or two-hand operation with adjustable HydraSmooth™ dual levers that automatically return to neutral from either forward or reverse position.
Brakes		Dynamic braking through hydrostatic transmission.
Parking Brake		Disc brake, one for each drive wheel.
Attachment Drive		NA
TIRE SIZES		
MidMount		
Drive Wheels - Standard (4-ply rated)	- 41" Deck	NA
	- 44" Deck	NA
	- 48" Deck	NA
	- 52" Deck	23x10.50x12 turf
	- 61" Deck	23x10.50x12 turf (*24x12.00x12 turf available as option)
	- 72" Deck	NA
Drive Wheels – Optional (4-ply rated)		NA
Front Wheels – All Models		13x6.50x6 rib tread, tubeless with double-sealed bearings.
FrontMount		
Drive Wheels – Standard (4-ply rated)		NA
Drive Wheels – Optional (4-ply rated)		NA
Single Tail Wheel		NA
Wide Stance Single Fork Tail Wheel		NA
Deck Tires (4-ply rated)	- 41" Deck	NA
	- 44" Deck	NA
	- 48" Deck	NA

- 52" Deck	NA
- 61" Deck	NA
- 72" Deck	NA

DIMENSIONS

Height (Seat Back) 45.0 in. (114.3 cm)

Height (Seat Cushion) 30.5 in. (77.5 cm)

Height (ROPS) 69.0 in. (175.3 cm)

Length (MidMount or FrontMount w/ DuraMax Deck) - 41" Deck NA

(Deck in Mowing Position) - 44" Deck NA

- 48" Deck NA

- 52" Deck 76.5 in. (194.3 cm)

- 61" Deck 79.0 in. (200.7 cm)

- 72" Deck NA

Length (FrontMount Power Unit + DuraMax Deck) - 44" Deck NA

(Deck Raised - Flipped) - 48" Deck NA

- 52" Deck NA

- 61" Deck NA

- 72" Deck NA

Deck Width (Side Discharge) - 41" Deck NA

- 44" Deck NA

- 48" Deck NA

- 52" Deck 65.5 in. (166.4 cm)

- 61" Deck 74.5 in. (189.2 cm)

- 72" Deck NA

Deck Width (Mulch*) - 41" Deck NA

- 44" Deck NA

- 48" Deck NA

- 52" Deck 53.5 in.* (135.8 cm)

- 61" Deck 62.5 in.* (158.8 cm)

- 72" Deck NA

FrontMount PowerUnit Only (Width/Length) NA

FrontMount Power Unit (Wheelbase) NA

WEIGHT - MidMount or FrontMount with DuraMax

(Uncrated) - 41" Deck NA

- 44" Deck NA

- 48" Deck NA

- 52" Deck 980 lbs. (444.5 kg)

- 61" Deck 1050 lbs. (476.3 kg)

- 72" Deck NA

FrontMount Power Unit Only (uncrated) NA

FrontMount Deck Only - Side Discharge (uncrated) - 41" Deck NA

- 44" Deck NA

- 48" Deck NA

- 52" Deck NA

- 61" Deck NA

- 72" Deck NA

Mulching Package - 41" Deck NA

- 44" Deck NA

- 48" Deck NA

- 52" Deck 29 lbs. (13.2 kg)

- 61" Deck 36 lbs. (16.3 kg)

- 72" Deck NA

*** Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised.**

All specifications and information displayed on this Web site are subject to change without notice.